

Time to Delivery Analysis on Follow-Up qPCR Data

Christof Seiler

3 February 2020

Contents

1	Goal	2
2	Prerequisites	2
3	Import Data	2
4	Fit Model.	3
4.1	RGS13.	3
4.2	IFNL	7
	Session Info	11

Time to Delivery Analysis on Follow-Up qPCR Data

1 Goal

Analyze data from qPCR experiments.

2 Prerequisites

Install necessary packages from bioconductor repository. Run this code only once to install packages.

```
pkgs_needed = c("ggplot2", "magrittr", "readr", "dplyr",
                "readxl", "stringr", "tidyR", "car",
                "interactions", "ggthemes", "cowplot",
                "MASS", "boot")
letsinstall = setdiff(pkgs_needed, installed.packages())
if (length(letsinstall) > 0) {
  source("http://bioconductor.org/biocLite.R")
  biocLite(letsinstall)
}
```

Load packages.

```
library("magrittr")
library("ggplot2")
library("readr")
library("dplyr")
library("readxl")
library("stringr")
library("tidyR")
library("MASS")
library("interactions")
library("ggthemes")
library("cowplot")
library("car")
library("boot")
theme_set(theme_few())
scale_colour_discrete = function(...) scale_colour_few()
if(params$treatment == "H1N1") {
  color_condition = "#FAA43A"
} else {
  color_condition = "#5DA5DA"
}
params$treatment
## [1] "mock"
```

3 Import Data

Read, merge, and tidy sample tables.

```
sample_info_filename = "MSS Case_Control Matches (Masked)_new_matched.xlsx"
data_filename = "PTB Raw qPCR data.xlsx"
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
new_matched = read_excel(sample_info_filename)
new_matched %>% mutate(time_to_delivery_calc =
    gestage_enroll - gestage_delivery)
qpcr_data = read_excel(data_filename)
qpcr_data$SampleID %>% as.character
qpcr_data %>% dplyr::left_join(new_matched, by = "SampleID",
    suffix = c("", "2"))
qpcr_data %>% dplyr::select(sample_id = SampleID,
    ptb_case,
    time_to_delivery = time_to_delivery_calc,
    gestage_delivery,
    RGS13_baseline,
    IFNL_baseline,
    IFNL_flu)
qpcr_data %>% gather(RGS13_baseline, IFNL_baseline, IFNL_flu,
    key = "key", value = "expr")
qpcr_data %>% mutate(
    treatment = if_else(condition = str_detect(qpcr_data$key, "baseline"),
        true = "mock",
        false = "H1N1"))
qpcr_data %>% mutate(
    gene_name = sapply(strsplit(qpcr_data$key, split = "_"),
        function(str) str[[1]]))
qpcr_data %>% dplyr::select(-key)
qpcr_data$treatment = factor(qpcr_data$treatment, levels = c("mock", "H1N1"))
qpcr_data %>% rename(ptb = ptb_case)
qpcr_data
## # A tibble: 165 x 7
##   sample_id ptb   time_to_delivery gestage_delivery     expr treatment
##   <chr>     <chr>           <dbl>            <dbl>    <dbl> <fct>
## 1 1.1       cont~          -6.57           37.6  0.160  mock
## 2 1.2       case           -5.57           21.3  0.0876 mock
## 3 1.3       cont~          -27.4            42.4  0.00572 mock
## 4 2.1       case           -18.3            33.6  0.0540  mock
## 5 2.2       cont~          -21.9            37.4  0.00703 mock
## 6 2.3       cont~          -24.3            39.3  0.00144 mock
## 7 3.2       cont~          -19.4            38    0.00470 mock
## 8 3.3       case           -14.7            33.4  0.0167  mock
## 9 4.3       cont~          -22.1            40    0.0529  mock
## 10 5.1      cont~          -21.9            40.9  0.0104 mock
## # ... with 155 more rows, and 1 more variable: gene_name <chr>
```

4 Fit Model

4.1 RGS13


Subset to RGS13.

Time to Delivery Analysis on Follow-Up qPCR Data


```
qpcr_data_RGS13 = qpcr_data %>% dplyr::filter(gene_name == "RGS13")
table(qpcr_data_RGS13$gene_name)
## 
## RGS13
##      55
```

Plotting to see possible outliers.

```
ggplot(qpcr_data_RGS13,aes(expr)) +
  geom_histogram(bins = 30) +
  facet_wrap(~ptb) +
  ggtitle("RGS13")
```




```
ggplot(qpcr_data_RGS13,aes(x = time_to_delivery, y = expr,
                           color = treatment)) +
  geom_smooth(method = lm, se = FALSE) +
  geom_point() +
  geom_text(aes(label = ifelse(expr > quantile(expr, probs = 0.95),
                     sample_id, "")), hjust = 0, vjust = 0) +
  ggtitle("RGS13")
```



```
ggplot(qpcr_data_RGS13,aes(x = gestage_delivery, y = expr,
                           color = treatment)) +
  geom_smooth(method = lm, se = FALSE) +
  geom_point() +
  geom_text(aes(label = ifelse(expr > quantile(expr, probs = 0.95),
                     sample_id, "")), hjust = 0, vjust = 0) +
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
ggtitle("RGS13")
```



Fit model for RGS13.

```
lm_fit = lm(expr ~ time_to_delivery + gestage_delivery, qpcr_data_RGS13)
summary(lm_fit)
##
## Call:
## lm(formula = expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_RGS13)
##
## Residuals:
##      Min       1Q   Median       3Q      Max 
## -0.08642 -0.02985 -0.01733  0.01426  0.32746 
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)    
## (Intercept) -0.104550  0.064954 -1.610  0.11354  
## time_to_delivery 0.004714  0.001974  2.388  0.02061 *  
## gestage_delivery 0.006059  0.002214  2.736  0.00848 ** 
## ---      
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1 
##
## Residual standard error: 0.06689 on 52 degrees of freedom
## Multiple R-squared:  0.131, Adjusted R-squared:  0.09754 
## F-statistic: 3.918 on 2 and 52 DF,  p-value: 0.026
```

Fit robust model using rank-based estimates of regression coefficients.

```
rlm_fit = rlm(expr ~ time_to_delivery + gestage_delivery, qpcr_data_RGS13)
summary(rlm_fit)
##
## Call: rlm(formula = expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_RGS13)
##
## Residuals:
##      Min       1Q   Median       3Q      Max 
## -0.04962 -0.02148 -0.01265  0.02540  0.36320 
##
## Coefficients:
##             Value    Std. Error t value    
## (Intercept) -0.0210   0.0383    -0.5479
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
## time_to_delivery 0.0025  0.0012      2.1358
## gestage_delivery 0.0026  0.0013      1.9913
##
## Residual standard error: 0.03594 on 52 degrees of freedom
```

Remove potential outlier and refit model to see if we still obtain a similar result.

```
qpcr_data_RGS13 %>% dplyr::filter(sample_id != "16.2")
lm_fit = lm(expr ~ time_to_delivery + gestage_delivery, qpcr_data_RGS13)
summary(lm_fit)
##
## Call:
## lm(formula = expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_RGS13)
##
## Residuals:
##       Min     1Q   Median     3Q    Max 
## -0.06230 -0.02892 -0.01508  0.01854  0.16243
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)    
## (Intercept) -0.041939  0.047497 -0.883   0.3814    
## time_to_delivery 0.002920  0.001441  2.026   0.0480 *  
## gestage_delivery 0.003507  0.001631  2.150   0.0363 *  
## ---      
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.04805 on 51 degrees of freedom
## Multiple R-squared:  0.09024,   Adjusted R-squared:  0.05456 
## F-statistic: 2.529 on 2 and 51 DF,  p-value: 0.08966
```


Plot of fitted intercept and slope with gestage_delivery fixed at its mean value.

```
coefs = coef(lm_fit)
gmine = ggplot(qpcr_data_RGS13,
                aes(x = time_to_delivery, y = expr,
                     shape = ptb, color = treatment)) +
  geom_point(size = 2) +
  scale_colour_manual(values = color_condition)

mean_gestage = mean(qpcr_data_RGS13$gestage_delivery)

gmine + geom_abline(intercept = coefs["(Intercept)"] +
                      mean_gestage*coefs["gestage_delivery"],
                      slope = coefs["time_to_delivery"],
                      color = color_condition, size = 1) + ggtitle("RGS13")
```

Time to Delivery Analysis on Follow-Up qPCR Data




4.2 IFNL

Subset to IFNL.

```
qpcr_data_IFNL = qpcr_data %>%
  dplyr::filter(gene_name == "IFNL") %>%
  dplyr::filter(treatment == params$treatment)
```


Plotting to see possible outliers.

```
ggplot(qpcr_data_IFNL,aes(expr)) +
  geom_histogram(bins = 30) +
  facet_wrap(~ptb) +
  ggtitle("IFNL")
```




```
ggplot(qpcr_data_IFNL,aes(x = time_to_delivery, y = expr,
                           color = treatment)) +
  geom_smooth(method = lm, se = FALSE) +
  geom_point() +
  geom_text(aes(label = ifelse(expr > quantile(expr, probs = 0.95),
                  sample_id, "")), hjust = 0, vjust = 0) +
  ggtitle("IFNL")
```

Time to Delivery Analysis on Follow-Up qPCR Data



```
ggplot(qpcr_data_IFNL, aes(x = gestage_delivery, y = expr,
                           color = treatment)) +
  geom_smooth(method = lm, se = FALSE) +
  geom_point() +
  geom_text(aes(label = ifelse(expr > quantile(expr, probs = 0.95),
                           sample_id, "")), hjust = 0, vjust = 0) +
  ggtitle("IFNL")
```



Fit model for IFNL.


```
lm_fit = lm(expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_IFNL)
summary(lm_fit)
##
## Call:
## lm(formula = expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_IFNL)
##
## Residuals:
##      Min       1Q   Median       3Q      Max 
## -0.024599 -0.012740 -0.007452 -0.001961  0.160878 
##
## Coefficients:
##             Estimate Std. Error t value Pr(>|t|)    
## (Intercept) 0.0408508  0.0293275  1.393   0.170    
## time_to_delivery 0.0004611  0.0008913  0.517   0.607    
## gestage_delivery -0.0005373  0.0009997 -0.537   0.593    
## 
## Residual standard error: 0.0302 on 52 degrees of freedom
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
## Multiple R-squared:  0.03729,    Adjusted R-squared:  0.0002618
## F-statistic: 1.007 on 2 and 52 DF,  p-value: 0.3723
```

Fit robust linear model fit and bootstrap resampling for confidence intervals and *p*-values.

```
lm_fit_robust = rlm(expr ~ time_to_delivery + gestage_delivery,
                     data = qpcr_data_IFNL, maxit = 200)
summary(lm_fit_robust)
##
## Call: rlm(formula = expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_IFNL,
##           maxit = 200)
## Residuals:
##      Min        1Q    Median        3Q       Max
## -0.006972 -0.004754 -0.002150  0.004525  0.172038
##
## Coefficients:
##             Value Std. Error t value
## (Intercept) 0.0078  0.0066    1.1872
## time_to_delivery 0.0001  0.0002    0.2646
## gestage_delivery 0.0000  0.0002   -0.0254
##
## Residual standard error: 0.00682 on 52 degrees of freedom
# bootstrap confidence interval and p-value
set.seed(0xdada)
lm_fit_robust_boot = Boot(lm_fit_robust, R = 1999)
summary(lm_fit_robust_boot)
##
## Number of bootstrap replications R = 1999
##          original   bootBias   bootSE   bootMed
## (Intercept) 7.8003e-03 9.6065e-04 0.01075449 7.7908e-03
## time_to_delivery 5.2830e-05 2.6155e-05 0.00028394 5.9898e-05
## gestage_delivery -5.6898e-06 -6.7112e-06 0.00033346 -6.2906e-06
hist(lm_fit_robust_boot, legend="separate")
```



```
Confint(lm_fit_robust_boot, level = 0.95, type = "perc")
## Bootstrap percent confidence intervals
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
##                                     Estimate      2.5 %    97.5 %
## (Intercept)    7.800291e-03 -0.0071847420 0.0296569633
## time_to_delivery 5.282996e-05 -0.0004260056 0.0007422489
## gestage_delivery -5.689807e-06 -0.0006310435 0.0006546222
Confint(lm_fit_robust_boot, level = 0.95, type = "bca")
## Bootstrap bca confidence intervals
##
##                                     Estimate      2.5 %    97.5 %
## (Intercept)    7.800291e-03 -0.0061546661 0.0341378634
## time_to_delivery 5.282996e-05 -0.0004095204 0.0008017508
## gestage_delivery -5.689807e-06 -0.0005988178 0.0006742549
# p-value for stimulation x time to delivery interaction term
R = 1999
t_obs = lm_fit_robust_boot$t0["time_to_delivery"]
t_boot = lm_fit_robust_boot$t[, "time_to_delivery"]-t_obs
pvalue = (1 + sum(abs(t_boot) > abs(t_obs))) / (R + 1)
pvalue
## [1] 0.816
```

Refit linear model after removing possible outlier.


```
qpcr_data_IFNL_with_outlier = qpcr_data_IFNL
lm_fit = lm(expr ~ time_to_delivery + gestage_delivery,
             data = qpcr_data_IFNL %>%
               dplyr::filter(sample_id != "1.1"))
summary(lm_fit)
##
## Call:
## lm(formula = expr ~ time_to_delivery + gestage_delivery, data = qpcr_data_IFNL %>%
##       dplyr::filter(sample_id != "1.1"))
##
## Residuals:
##      Min        1Q        Median        3Q       Max
## -0.024237 -0.011042 -0.007063 -0.001783  0.162282
##
## Coefficients:
##                               Estimate Std. Error t value Pr(>|t|)
## (Intercept)          0.0465914  0.0290324   1.605   0.115
## time_to_delivery  0.0001085  0.0009011   0.120   0.905
## gestage_delivery -0.0008509  0.0010004  -0.851   0.399
##
## Residual standard error: 0.02969 on 51 degrees of freedom
## Multiple R-squared:  0.0365, Adjusted R-squared:  -0.001281
## F-statistic: 0.9661 on 2 and 51 DF,  p-value: 0.3874
```

Residual plots.

```
tb_subset = qpcr_data_IFNL
rlm_delivery = rlm(expr ~ gestage_delivery, data = tb_subset)
tb_subset %>% mutate(residual_expr = rlm_delivery$residuals)
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
rlm_delivery = rlm(residual_expr ~ time_to_delivery, data = tb_subset)
a = rlm_delivery$coefficients[[1]]
b = rlm_delivery$coefficients[[2]]
tb_subset %>% mutate(y_hat = a + b*tb_subset$time_to_delivery)
gmine_with_outlier = ggplot(tb_subset, aes(time_to_delivery, residual_expr,
                                             color = ptb)) +
  geom_abline(intercept = a, slope = b, color = color_condition, size = 1) +
  geom_point() +
  ggtitle(paste0("IFNL - ", params$treatment)) +
  xlab("time to delivery") +
  ylab("residual expression") +
  theme(legend.position = "bottom")
gmine_with_outlier
```



```
save(gmine_with_outlier,
      file = paste0("robust_fit_IFNL_", params$treatment, ".Rdata"))
```

Session Info

```
sessionInfo()
## R version 3.5.1 (2018-07-02)
## Platform: x86_64-apple-darwin15.6.0 (64-bit)
## Running under: macOS 10.15.3
##
## Matrix products: default
## BLAS: /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/3.5/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## attached base packages:
## [1] stats      graphics   grDevices  utils      datasets   methods    base
```

Time to Delivery Analysis on Follow-Up qPCR Data

```
##  
## other attached packages:  
## [1] boot_1.3-22      car_3.0-3       carData_3.0-2  
## [4] cowplot_1.0.0    ggthemes_4.1.1   interactions_1.1.1  
## [7] MASS_7.3-51.4    tidyverse_1.3.0  stringr_1.4.0  
## [10] readxl_1.3.1    dplyr_0.8.3    readr_1.3.1  
## [13] ggplot2_3.2.1    magrittr_1.5   BiocStyle_2.10.0  
##  
## loaded via a namespace (and not attached):  
## [1] tidyselect_0.2.5  xfun_0.6        purrr_0.3.3  
## [4] pandoc_2.1.1     haven_2.1.0     colorspace_1.4-1  
## [7] vctrs_0.2.1      generics_0.0.2  htmltools_0.3.6  
## [10] yaml_2.2.0       utf8_1.1.4     rlang_0.4.2  
## [13] pillar_1.4.3    foreign_0.8-71 glue_1.3.1  
## [16] withr_2.1.2     jtools_2.0.1    lifecycle_0.1.0  
## [19] munsell_0.5.0    gtable_0.3.0   cellranger_1.1.0  
## [22] zip_2.0.2       evaluate_0.13  labeling_0.3  
## [25]forcats_0.4.0    knitr_1.22     rio_0.5.16  
## [28] curl_4.3        fansi_0.4.1    Rcpp_1.0.3  
## [31] scales_1.1.0    backports_1.1.5 BiocManager_1.30.4  
## [34] abind_1.4-5     farver_2.0.1   hms_0.5.2  
## [37] digest_0.6.23   openxlsx_4.1.0.1 stringi_1.4.5  
## [40] bookdown_0.9    grid_3.5.1     cli_2.0.1  
## [43] tools_3.5.1     lazyeval_0.2.2  tibble_2.1.3  
## [46] crayon_1.3.4    pkgconfig_2.0.3 zeallot_0.1.0  
## [49] ellipsis_0.3.0   data.table_1.12.6 assertthat_0.2.1  
## [52] rmarkdown_1.12    R6_2.4.1      compiler_3.5.1
```